



2" LEG LENGTH

PREDRILLED FOR THRU BOLTING

ANCHOR FLOOR PLATES

$\frac{3}{16}$ " BACK UP PLATE FOR HARDWARE

SPECIFICATIONS:

- WALL THICKNESS:
- WALL TYPE:
- FINISHED OPENING SIZE:

TO CALCULATE A ROUGH OPENING:

- FINISHED WIDTH & ADD $1\frac{1}{4}$ " =
- FINISHED HEIGHT & ADD $\frac{5}{8}$ " =

MATERIAL TYPE 304B-2B

- 12 GA. POLISHED STAINLESS STEEL
- 12 GA. PRIMED MILD STEEL

UNIT(S) REQUIRED: _____

FOR FABRICATION : _____ FOR APPROVAL: _____

STEEL (STD) OPTIONAL STAINLESS STEEL GALV.

ALL HOLES ARE PRE-DRILLED IN FRAME FOR QUICK AND EASY INSTALLATION.

DIMENSION "A" = _____

DIMENSION "B" = _____

DOOR MODEL # _____

MISC. NOTES _____

MODEL # 12 GA. C-CHANNEL JAMB WRAP



©COPYRIGHT 2000
CHASE INDUSTRIES, INC.
SPECIFICATIONS SUBJECT TO
CHANGE WITHOUT NOTICE.
1 800-543-4455
www.chasedoors.com

CUSTOMER INFORMATION:

DATE: 5/5/2006 CHASE APPROVAL

FORM # SD4590

REV.