



SECTION "AA"
OF DOOR

SPECIFICATIONS:

DOOR SHOWN AS ALUMINUM SHEET STYLE SERVICE DOOR, DOUBLE ACTING, SHALL BE MODEL SD-2000 CAFE DOOR AS MANUFACTURED BY CHASE INDUSTRIES, INC., CINCINNATI, OHIO, TO FIT DOOR OPENING _____ WIDE BY _____ HIGH.

DOOR SHALL BE CONSTRUCTED OF .063" THICK ALUMINUM WITH ANODIZED ALUMINUM FINISH. BOTH SIDES.

DOOR TO HAVE 1" THICK x 2.5" WIDE BACK EDGE REINFORCEMENT SPINE. BACK EDGE SPINE SHALL HAVE PLYWOOD CORE AND BE CLAD WITH PROPER ALUMINUM TO MATCH DOOR BODY.

COMPLETE WITH CHASE GRAVITY-OPERATED HINGING SYSTEM WITH 5/8" DIAMETER STEEL HINGE PIN AND 1" DIAMETER DELRIN CAM. BOTH TOP AND BOTTOM HINGES HAVE 3/16" THICK STEEL ANGLE AND MOUNT DIRECTLY THROUGH DOOR BODY.

SPECIFY RIGHT OR LEFT HAND SWING

NO WINDOW (VISION PANEL)

NO IMPACT PLATES

BUMPER OPTIONS (BOTH SIDES ONLY):

PVC STRIP (SPECIFY COLOR) _____ ALUM. STRIP (SPECIFY LOCATION) _____

MODEL # SD2000, CAFE SINGLE PANEL SHEET STYLE SERVICE DOOR

©COPYRIGHT 2000 CHASE INDUSTRIES, INC. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
1 800-543-4455
www.chasedoors.com

CUSTOMER INFORMATION:

Chase Doors
World's Leading Manufacturer Of Traffic Doors
Cincinnati Ohio, and Redmond Oregon
Phone Toll Free: 1-800-543-4455

DATE: 7/14/00 CHASE APPROVAL

FORM # SD4007

REV. A