



SPECIFICATIONS:

DOORS SHOWN AS STAINLESS STEEL SHEET STYLE SERVICE DOORS, DOUBLE ACTING, SHALL BE MODEL SST-2000 DOORS AS MANUFACTURED BY CHASE INDUSTRIES, INC., CINCINNATI, OHIO, TO FIT DOOR OPENING _____ WIDE BY _____ HIGH.

DOOR SHALL BE CONSTRUCTED OF 16 GA. STAINLESS STEEL WITH #4 BRUSHED FINISH. BOTH SIDES.

PANELS SHALL BE MANUFACTURED WITH A ONE PIECE BACK EDGE SPINE OF CONTINUOUS EXTRUDED ALUMINUM WITH FLANGES THAT RADIUS THE DOOR PANEL. THE SPINE IS POWDER COATED BLACK. STANDARD HINGE SYSTEM CONSISTS OF THE FOLLOWING COMPONENTS: UPPER HINGE: SPRING LOADED, LOW FRICTION WITH UHMW PLUG. LOWER HINGE: LOW FRICTION UHMW CAM MATED TO A STAINLESS STEEL CAM WHICH HAS AN ADJUSTMENT FOR CENTERING PANEL IN OPENING. SPINE: ALL MOVING HINGE PARTS ARE FULLY ENCLOSED WITH THE EXTRUDED ALUMINUM SPINE.

ACRYLIC VISION PANEL TO BE 1/4" TH. x 9" x 14" SET IN BLACK RUBBER MOLDING (STD).

INCLUDE OPTIONS AS INDICATED BELOW:
 3-3/4"x8-3/4" HIGH ALUM. JAMB GUARDS

IMPACT PLATE (BOTH SIDES): YES NO
 STAINLESS STEEL IMPACT PLATES
 STAINLESS STEEL/GALVANIZED IMPACT PLATES
 PLASTIC IMPACT PLATES
 (SPECIFY COLOR:) FOREST GREEN JADE
 CADET BLUE WHITE GRAY CLOUD GRAY
 CHOCOLATE RED MEDIUM BROWN NAVY
 ROYAL BLUE BLACK BEIGE BURGUNDY
 IMPACT PLATE HEIGHT:
 12" 18" 24" 36" 48"

BUMPER OPTIONS (BOTH SIDES ONLY):
 STANDARD TEARDROP CROSS-LINKED POLYETHYLENE (SPECIFY COLOR) _____ (AND HEIGHT) _____
 PVC STRIP (SPECIFY COLOR) _____ ALUM. STRIP (SPECIFY LOCATION) _____

MODEL # SST-2000, BIPARTING SHEET STYLE SERVICE DOOR



@COPYRIGHT 2000 CHASE INDUSTRIES, INC. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. 1 800-543-4455 www.chasedoors.com

CUSTOMER INFORMATION:

DATE: 4/12/05 CHASE APPROVAL

FORM # SD4259

REV. A